

CASH DRAWER



PRODUCT FEATURES



Metal Case

ZQ-410F

This series of cashbox has compatibility, stainless steel enclosure and Rj-11 interface. The relevant settings have the 3,4,5 paper currency slots and 8 coin spaces available.

HIGHLIGHTS

- With metal tray
- · 3-position locks
- Noiseless track
- · With check slot
- Separated pulled out drawer box for cash and coins



Adjustable bill and coin slot



3 level solid lock

SPECIFICATIONS			
Surface treatment process	Powder coating on cashbox surface	Check slot	1
Color	Black	Working condition	-5-55 ℃ ,5-85%RH
Standard bill slot	5 (5 metal slots)	Service life	1million times 25% energization
Optional bill slot	4	Maximum load of cash drawer	4KG
Standard coin slot	8	Maximum load of cash box	40KG
Drive voltage	12v(9.5-24vcompatible)	Tension of pull out the cash drawer	1.0±0.2KG
Rated current	1.5A±10%	Cash joint	RJ11 6P4C
Rated power	18W	Cashbox dimension	410(W)×416(L)×100(H)
Coil resistance	8Ω±10%	Carton sizes	465(W)×460(L)×150(H)
Tractive effort	1mm≥800gf 3mm≥500gf	Net weight	7.0KG
Withstand voltage	AC 1200V(50/60Hz) 1sec between	Gross weight	8.0KG
	the coil and the frame	Electromagnetic switch wire	4 core cable;0.5kgf(60sec)
Temperature rise	Max temperature rise 65℃ (under	core and tensile strength	
	nominal voltage)	Cable length	140mm
Working cycle	Intermittent electricity ON:1sec, OFF:4sec	Drawer material	Plastics
Insulation resistance	$1000M\Omega$ between the coil and the frame	Tray material	Metal
	(5000DVC under normal temperature)	Cashbox lock	3-position key locks