



## CUSTOMER POLE DISPLAY

### ZQ-VFD2600

The customer display series is compatible with the Epson mode, with a three-level adjustable height. The power supply adapter is optional.

### HIGHLIGHTS

- EPSON emulation compatible
- Support Chinese character & graphic displaying
- 3 level pole for length adjusting
- Adaptor of wide power input range for easy using



## APPLICATION REFERENCE

Zonerich Customer Pole display is widely used in kind of POS solutions:

- Hospitality solutions
- Retail Cashier Systems
- Car Parking Systems



## SPECIFICATIONS

Display Method	Vacuum Fluorescent Display	COM Port(Optional)	Baud rate from 2400BPS to 19200BPS (9600BPS as default)
Display Type	24(Lines) x 120(Columns)	Power	DC 12V, 1A
Language Supported	English	Power Consumption	<4W
Characters Font	10 Characters/line (Font: 12X12) 20 Characters/line (Font: 6X12)	Environment	Work Temp. and Humidity: -10~55°C, 35~85%RH Storage Temp. and Humidity: -20~65°C, 10~85%RH
Character Set	96 ASCII	Height Supported	170mm, 170+120mm, 170+120+120mm
Emit Color	Green	Display Panel Sizes	206x118x283mm
Drive Mode	Dynamic	Display Base Sizes	206x118x403mm
Audio	No	Package Sizes	206x118x523mm
Emulation	EPSON, Norriake, futaba, PL-200, UTC Standard, ENHANCE, AEDEX, ADM788, DSP800, CD5220 (PTC), LOGIC, POS7300, UTC, EMAX	Weight	1.0kg
Elevation	0~90°		
Ports	1x USB, 1XRS232(Optional)		